



PRODUCT INFORMATION

CADAOIL CLASSIC 15W-40 SF-CC

Mineral motor oil for gasoline, LPG and diesel engines

Cadaoil Classic 15W-40 SF-CC is formulated with shear-stable viscosity improvers to prevent viscosity drops after some time. Because of this, a strong and stable lubricant film is guaranteed, even at high temperatures.

Classic 15W-40 SF-CC contains deterging and dispersing additives, keeping the oil and the engine clean, even the most critical parts. Corrosion and sludge are reduced to a minimum, while anti-wear additives, together with the high quality base oils, offer maximum protection to heavily loaded parts.

Classic 15W-40 SF-CC has a long life-time and assures a low oil consumption. This oil can be used in all gasoline and LPG engines, as well in light duty, non-turbo charged diesel engines.

Classic 15W-40 SF-CC is especially suitable for older cars as running-in motor oil.

PERFORMANCE

API SF/CD
MIL-L-2104D
Ford WSS-M2C153-D
MIL-L-46152C
GM 6049-M
GM 6048-M

Density at 20°C	0,8645 kg/l
Viscosity, kinematic at 100°C	14,5 cSt
Viscosity, kinematic at 40°C	105,9 cSt
Viscosity Index	141
Viscosity, dynamic (CCS)	5960 cP
Sulphated ash	0,77 wt%
Flash point	205 °C
Freezing point	-27 °C

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.