



PRODUCT INFORMATION

CADAOIL GEARBOX 75W-90 GL 4/5

Synthetic transmission oil for manual gearboxes and final drives

Gearbox 75W-90 GL4/5 is a synthetic, universal transmission/gear oil which can be applied in both manual gearboxes as well as in final drives, where an API GL-3, 4 or 5 quality oil is prescribed. By this, the product can reduce the stock of transmission/gear oils.

Gearbox 75W-90 GL4/5 can be used for the complete drive line. The product contains special additives reducing fuel consumption and eliminating shifting problems. Due to this unique formulation not only wear, but also corrosion and foam building are reduced to a minimum. At high temperatures the oil is protected against thermal oxidation.

Gearbox 75W-90 GL4/5 can be used in synchromesh gearboxes and ensures easy and smooth shifting, even at low temperatures.

Gearbox 75W-90 GL4/5 shows excellent EP (Extreme Pressure) characteristics to cope with heavy loads and vibrations. Viscosity drop, caused by heavy loads, is minimal so that this oil guarantees the right viscosity, even at prolonged drain intervals.

PERFORMANCE

API MT-1

API GL 3/4/5

MIL-L-2105 B/C/D

ZF TE-ML 02B/05A/07A/08A/12E/16B/ 16C/16D/17B/19B/21A

Mack GO-J

MIL-PRF-2105E

Volvo 97310

Scania STO 1:0

DAF

MAN M 3343 Typ M

MAN 342 Type M2

MAN 341 Type Z2

MB 235.1

MB 235.0

Arvin Meritor 076-N

IVECO

Density at 20°C	0,8825 kg/l
Viscosity, kinematic at 100°C	15 cSt
Viscosity, kinematic at 40°C	86,7 cSt
Viscosity Index	183
Flash point	144 °C

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.