



PRODUCT INFORMATION

CADAOIL GRAPHITE 10W-30 SL/CF

Synthetic universal fuel saving motor oil

Cadaoil Graphite 10W-30 SL/CF is a synthetic engine oil recommended for petrol and diesel engines. Because of the high viscosity index, the oil assures an excellent cold start as well as an excellent lubricating film with high temperatures. This oil is not suitable for diesel engines equipped with DPF (Diesel Particle Filter)

Cadaoil Graphite 10W-30 SL/CF gives optimum protection against wear and has strong anti - corrosion and anti-foam characteristics as well as a high resistance against oxidation. Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

PERFORMANCE

Performance level

API SL/CF

Recommended for use

ACEA A3/B4-04

MB 229.1

VW 501.01

VW 505.00

Colour	Brown	
Density at 20°C	0.8629 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	76.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.7 cSt	ASTM D 445
Viscosity Index	147	ASTM D 2270
Viscosity, dynamic (CCS)	5590 cP	ASTM D 2602
Base number	8.0 mg KOH/g	ASTM D 2896
Sulphated ash	0.95 wt%	ASTM D 874
Flash point	200 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.