



PRODUCT INFORMATION

CADAOIL GRAPHITE 20W-50

Universal Synthetic Motor Oil

Cadaoil Graphite 20W-50 is a synthetic engine oil suitable for petrol as well as for diesel engines. Because of the high viscosity index, the oil assures an excellent cold start and an excellent lubricating film at high temperatures.

Graphite 20W-50 takes care of trouble free functioning of the engine, because of the chosen additive package. The oil helps reducing the fuel consumption as well as reducing emission levels.

Due to the unique formulation a low evaporation under severe operating conditions is guaranteed. In addition, Cadaoil Graphite 20W-50 gives optimum protection against wear and has strong anti - corrosion and anti-foam characteristics as well as a high resistance against oxidation. Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

PERFORMANCE

API SL/CF
ACEA A3/B4-04 MB 229.1
VW 501.01
VW 505.00

Colour	Brown	
Density at 20°C	0.8735 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	145.6 cSt	ASTM D 445
Viscosity, kinematic at 100°C	17.7 cSt	ASTM D 445
Viscosity Index	134	ASTM D 2270
Viscosity, dynamic (CCS)	5276 cP	ASTM D 2602
Base number	8.0 mg KOH/g	ASTM D 2896
Sulphated ash	0.95 wt%	ASTM D 874
Flash point	208 °C	ASTM D 93
Pour point	-30 °C	ASTM D 97

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.