



PRODUCT INFORMATION

CADA OIL GRAPHITE 5W-30 SYNTH

Fully synthetic oil for gasoline and diesel engines, with or without turbo

Graphite 5W-30 Synth is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied to cars equipped with catalytic converters, turbo charged engines or for direct fuel injection systems.

Graphite 5W-30 Synth quickly forms a stable lubricant film during cold cranking and offers high thermal stability under heavy duty operating conditions.

Graphite 5W-30 Synth not only offers an extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits

Graphite 5W-30 Synth offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

PERFORMANCE

API SM/CF
ACEA A3/B3
ACEA A3/B4-08
VW 502.00
VW 505.00
MB 229.3
BMW Longlife-98
Porsche A40
Renault RN0710
Renault RN0700

Density at 20°C	0,8535 kg/l
Viscosity, kinematic at 100°C	11,1 cSt
Viscosity, kinematic at 40°C	66,2 cSt
Viscosity Index	161
Viscosity, dynamic (CCS)	5800 cP
Flash point	226 °C
Freezing point	-42 °C

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.