



## PRODUCT INFORMATION

### **CADAOIL GRAPHITE 5W-40 A3/B4**

Fully synthetic motor oil for gasoline and diesel engines, with or without turbo

Graphite 5W-40 A3/B4 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied to cars equipped with catalytic converters, turbo charged engines or for direct fuel injection systems.

Graphite 5W-40 A3/B4 quickly forms a stable lubricant film during cold cranking and offers high thermal stability under heavy duty operating conditions.

Graphite 5W-40 A3/B4 not only offers an extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits

Graphite 5W-40 A3/B4 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

### **PERFORMANCE**

API SN/CF  
ACEA A3/B4  
VW 502.00;VW 505.00  
MB 229.3; GM-LL-B-025  
PSA B71 2296 / PSA B71 2293  
Porsche A40  
Renault RN0710;Renault RN0700

#### Recommended for use

Fiat 9.55535-Z2  
Fiat 9.55535-N2  
Fiat 9.55535-M2  
Fiat 9.55535-H2

		<b>0W-40</b>	<b>5W-30</b>	<b>5W-40</b>	<b>5W-50</b>
Density 20C	Kg/L	0.843	0.851	0.852	0.851
Viscosity 100C	cSt	14.3	11.0	14.3	18.1
Viscosity 40C	cSt	83.2	65.0	85.9	112
Viscosity -30C	cP	-	<6600	<6600	<6600
Viscosity -35C	cP	<6200	-	-	-
Viscosity Index		179	162	173	179
Flash point COC	C	>210	>210	>220	>220
Pour point	C	<-54	<-36	<-36	<-36
Sulphated ash	Wt%	1.2	1.2	1.2	1.2

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.