



PRODUCT INFORMATION

CADA OIL PLATINUM STAGE 0W-30

Fully synthetic fuel economy long-life motor oil MB 229.5

Platinum Stage 0W-30 is a fully synthetic motor oil for use in passenger cars and light duty commercial vehicles. This oil can be used in cars with turbo charged engines, catalytic converters and direct fuel injection diesel engines.

Platinum Stage 0W-30 provides an extremely rapid and stable lubricant film at the cold start and maintains this film at high operating temperatures.

Platinum Stage 0W-30 also offers an extremely high oxidation stability and wear protection. Both engine and oil stay clean, even after prolonged drain intervals (up to 30.000 km).

Platinum Stage 0W-30 offers extra fuel saving properties and can be mixed with both synthetic and mineral motor oils, although especially for this oil, mixing with other oils will not benefit the outstanding quality of the products.

Platinum Stage 0W-30 meets the MB 229.5 specification and can be used for an intensive and prolonged use.

PERFORMANCE

API SL/CF
ACEA A3/B4
VW 502.00
MB 229.5
MB 229.3
Renault RN0710
Renault RN0700
VW 505.00
Volvo 95200356

Density at 20°C	0,8414 kg/l
Viscosity, kinematic at 100°C	12,2 cSt
Viscosity, kinematic at 40°C	68,2 cSt
Viscosity Index	179
Viscosity, dynamic (CCS)	5150 cP
Sulphated ash	209 wt%
Flash point	194 °C
Freezing point	-54 °C

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.