



PRODUCT INFORMATION

CADAOIL GOLD HD 20W-50

Mineral motor oil for mixed fleet

Cadaoil GOLD HD 20W-50 has been developed according to the latest oil consumption and exhaust emission requirements and protects against oil thickening and wear. Besides, it has an excellent deterging capability.

Cadaoil GOLD HD 20W-50 is especially suitable for mixed fleet applications like gasoline, LPG and light loaded diesel engines, whether or not turbo charged and/or with catalytic converter. Because of this broad applicability, this oil can reduce the stock level for the fleet owner and the retailer.

Cadaoil GOLD HD 20W-50 amply fulfils the latest, strict norms regarding deposits on piston crowns, in top piston ring grooves and on the rest of the pistons.

PERFORMANCE

API SJ/CG-4
MB 228.1 / MB 229.1
MAN 271
Volvo VDS
MTU type 1
Mack EO/L
VW 501.01/505.00 (97)

Recommended for use

ACEA B3-98 issue 2
ACEA E2-07
ACEA A2-02

Colour	Brown	
Density at 20°C	0.8809 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	154 cSt	ASTM D 445
Viscosity, kinematic at 100°C	17.6 cSt	ASTM D 445
Viscosity Index	125	ASTM D 2270
Viscosity, dynamic (CCS)	6560 cP	ASTM D 2602
Base number	8.2 mg KOH/g	ASTM D 2896
Sulphated ash	1.05 wt%	ASTM D 874
Flash point	225 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.