



PRODUCT INFORMATION

CADAOIL GOLD HD 50

Cadaoil GOLD HD 50 is specially developed for light and heavily loaded diesel engines whether or not turbo charged. This oil is also suitable for diesel engines that run on a higher Sulphur content (<0,5%).

Cadaoil GOLD HD 50 offers a good protection against wear, corrosion, sludge and foaming and stays stable even during high temperatures.

Cadaoil GOLD HD 50 is specially suitable for diesel engines where mono grade has been prescribed for several applications in agriculture and marine industries.

PERFORMANCE

API SL/CI-4 Level
MB 228.2 Level; MTU Type
2 Level; MAN M3275-2

Kleur	Bruin	
Dichtheid bij 20°C	0,892 kg/l	ASTM D 1298
Viscositeit, kinematisch bij 40°C	198,3 cSt	ASTM D 445
Viscositeit, kinematisch bij 100°C	19,1 cSt	ASTM D 445
Viscositeitindex	107	ASTM D 2270
Basegetal	11,0 mg KOH/g	ASTM D 2896
Vlampunt	200 °C	ASTM D 93
Pour point	-27 °C	ASTM D 97

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

38 Avenue De Waterloo 6000 Charleroi BELGIQUE | M +32 483 70 99 93 | F +32 71 50 27 34
E info@cadaoil.be | W www.cadaoil.be