

PRODUCT INFORMATION

CADAOIL GOLD LOW SAPS 10W-40

Synthetic UHPD motor oil, based on low SAPS technology

Cadaoil GOLD LOW SAPS 10W–40 is a synthetic motor oil for commercial vehicles based on the so called 'low SAPS' technology. This means that sulphur, phosphorus and sulphated ash concentrations are reduced radically, to protect the exhaust gas after treatment systems.

Especially Mercedes (228.51) and MAN (M3477) have set up special standards for the oil to meet Euro-4 and Euro-5 emission regulations, including reduced sulphur, phosphorus and sulphated ash concentrations. For this reason, ACEA launched the E6 specification at the end of 2004.

Cadaoil GOLD LOW SAPS 10W–40 has fuel economy properties and because of the special additive technology, both the oil and the engine are kept clean in an unprecedently way. In Euro–4, 5 and Euro–6 engines the harmful exhaust gas emission is reduced.

Cadaoil GOLD LOW SAPS 10W-40 is suitable for extended drain intervals, if allowed by the OEM and depending on working conditions and filtration methods, so it reduces maintenance cost.

Cadaoil GOLD LOW SAPS 10W-40 can also be applied in older trucks with Euro-3 engines, where ACEA E4, Mercedes 228.5 and MAN 3277 are prescribed, as well Renault RXD and DAF HP-2.

PERFORMANCE

Approved	Performance Level	
MB-Approval 228.51 MAN M 3477 MAN M 3271-1	API CI-4 ACEA E6 ACEA E7 MB 226.9 Volvo VDS-3 Renault RLD-2 Renault RXD CES 20076	Deutz DQC III-10 LA MTU type 3.1 Renault RGD DAF Mack EO-N JASO DH-2 CES 20077

Colour	Brown		
Density at 20°C	0.8583 kg/l	ASTM D 1298	
Viscosity, kinematic at 40°C	96.8 cSt	ASTM D 445	
Viscosity, kinematic at 100°C	14.5 cSt	ASTM D 445	
Viscosity Index	155	ASTM D 2270	
Viscosity, dynamic (CCS)	6620 cP	ASTM D 2602	
Base number	10.1 mg KOH/g	ASTM D 2896	
Sulphated ash	0.99 wt%	ASTM D 874	
Flash point	233 °C	ASTM D 93	
Pour point	-42 °C	ASTM D 97	

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

38 Avenue De Waterloo 6000 Charleroi BELGIQUE | M +32 483 70 99 93 | F +32 71 50 27 34 E info@cadaoil.be | W www.cadaoil.be