



PRODUCT INFORMATION

CADAOIL GOLD SHPD 10W-30

Cadaoil GOLD SHPD 10W-30 is a mid SAPS engine oil, developed according to the latest oil consumption and exhaust emission regulations. It meets all current quality requirements for European, American and Japanese diesel and gasoline engine oils.

Cadaoil GOLD SHPD 10W-30 is especially suitable for heavily loaded diesel engines, but can also be applied in gasoline engines

Cadaoil GOLD SHPD 10W-30 amply fulfils the latest strict norms regarding American trucks with and without EGR and diesel particle filter.

Due to its excellent oxidation stability and thermal stability as well as strong dispersing and deterging combination Cadaoil GOLD SHPD 10W-30 ensures both the oil and the engine to stay in good condition.

PERFORMANCE

API CJ-4	Caterpillar ECF-2
API SM	Caterpillar ECF-1-A
ACEA E9	CES 20081
MB 228.31	Deutz DQC III-10
MAN M 3275 Volvo VDS-4	MTU type 2.1
Renault RLD-3 Caterpillar	MAN M 3575
ECF-3	Mack EO-O PP

Colour	Brown	
Density at 20°C	0.8655 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	78.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	11.6 cSt	ASTM D 445
Viscosity Index	140	ASTM D 2270
Viscosity, dynamic (CCS)	5750 cP	ASTM D 2602
Base number	7.3 mg KOH/g	ASTM D 2896
Sulphated ash	0.99 wt%	ASTM D 874
Flash point	205 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.