



PRODUCT INFORMATION

CADA OIL GOLD SHPD 10W-40

Synthetic motor oil for mixed fleet

Cadaoil GOLD SHPD 10W-40 is a solid, synthetic motor oil and particularly suitable for heavily loaded commercial vehicles. But the product can also be applied in gasoline, LPG and light loaded diesel engines, whether or not turbo charged and/or with catalytic converter and/or common rail system.

Due to its fuel saving properties, Cadaoil GOLD SHPD 10W-40 meets a great number of leading OEM specifications and therefore is a perfect multifunctional motor oil for a mixed fleet.

Cadaoil GOLD SHPD 10W-40 amply fulfils the strict norms concerning combustion deposits on the piston crown, in the top piston ring groove and on the rest of the piston.

Due to the high temperature and ageing stability, as well the presence of strong deterging additives, Cadaoil GOLD SHPD 10W-40 ensures both the oil and the engine to stay in good condition.

Wear is limited to a minimum, even under the most severe working conditions, so the quality of Cadaoil GOLD SHPD 10W-40 is guaranteed during the full drain interval, regardless the type of engine.

The synthetic base stocks not only provide an uncomplicated cold start, but also offer fuel saving and less oil consumption because of less evaporation loss.

PERFORMANCE

Approved

Volvo VDS-3
Renault RLD-2
Mack EO-N

Performance Level

API SL/CI-4	MAN M 3275	Deutz DQC III-10
ACEA A3/B4	Renault RLD	Global DHD-1
ACEA E7	Caterpillar ECF-2	MTU type 2
Allison C-4	Caterpillar ECF-1-A	Detroit Diesel DDC 93K215
MB 235.27	CES 20077	MAN M 3271
MB 228.3	CES 20078	JASO DH-1
MB 229.1	Voith Class A	

Colour	Brown	
Density at 20°C	0.8646 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	98.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.9 cSt	ASTM D 445
Viscosity Index	158	ASTM D 2270
Viscosity, dynamic (CCS)	6120 cP	ASTM D 2602
Base number	10.4 mg KOH/g	ASTM D 2896
Sulphated ash	1.52 wt%	ASTM D 874
Flash point	210 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

This sheet contains recommendations or suggestions on properties and possible applications of Cadaoil products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

